



## 2022 Rule Change Summary

### Bowling

Change From	Change To
Old Formatting	See date change at footer to reflect October 2022
<p>2.1.2 Ramp Unassisted Bowl (one bowler)</p> <p>2.1.2.1 Athlete aims ramp into position unassisted</p> <p>2.1.2.2 Athlete positions ball on the ramp with assistance and pushes ball down ramp toward target.</p> <p>2.1.2.3 An assistant must have his/her back to the pins at all times.</p> <p>2.1.2.4 A bowler may be allowed to bowl up to three frames consecutively.</p> <p>2.1.3 Ramp Assisted Bowl (one bowler)</p> <p>2.1.3.1 An assistant may aim the ramp toward the pins, but must at all times have his/her back to the pins and aim based on direction (either verbally or by physical cues) from the athlete.</p> <p>2.1.3.2 A bowler may be allowed to bowl up to three frames consecutively.</p>	<p><b>CHANGE/ADD:</b> Combined language of 2.1.2 &amp; 2.1.3 for clarity. Included divisioning statement in 2.1.2.5.</p> <p>2.1.2 Ramp <del>Unassisted</del> Bowl (one bowler)</p> <p>2.1.2.1 Athlete aims ramp into position unassisted <b>or with the help with an assistant</b></p> <p>2.1.2.2 <b>Unassisted:</b> Athlete positions ball on the ramp with assistance and pushes ball down ramp toward target</p> <p>2.1.2.3 <b>Assisted:</b> An assistant must have his/her back to the pins at all times</p> <p><b>2.1.2.3.1 An assistant may aim the ramp towards the pins, but must at all times have his/her back to the pins and aim based on direction (either verbally or by physical cues) from the athlete</b></p> <p><b>2.1.2.4 A bowler may be allowed to bowl up to three frames consecutively</b></p> <p><b>2.1.2.5 Ramp Bowlers may be divisioned in the traditional events where entries are limited once the ability of the bowler is comparable with the others in the division.</b></p>
<p>3.4.2 3.4.2 Ramps are a two-piece metal unit, one stand and one sloped piece. The stand is a minimum height of 24 inches and maximum</p>	<p><b>CHANGE:</b> New maximum height requirement and removal of un-necessary slope specifications.</p>



height of 28 inches. The stand width is 24 to 25 inches across. Sloped piece: from connecting point to stand to first bend is 16 inches and from first bend to bottom of sloped piece is 54 inches.

3.4.2 3.4.2 Ramps are a two-piece metal unit, one stand and one sloped piece. The stand is a minimum height of 24 inches and maximum height of 30 inches. ~~Sloped piece: from connecting point to stand to first bend is 16 inches and from first bend to bottom of sloped piece is 54 inches.~~